

High-Speed Single or Dual-Sided Plastic Card Printer

By NBS Technologies

ImageMaster[™] D-40





HIGH-SPEED SINGLE OR DUAL-SIDED PLASTIC CARD PRINTER WITH FEATURES & PERFORMANCE THAT PERFORMS WELL IN EVEN THE MOST DEMANDING ENVIRONMENTS

THE IMAGEMASTER™ D-40 OFFERS THESE KEY FEATURES AND BENEFITS:



COMPACT AND FLEXIBLE

- Delivers fast monochrome printing: up to 4000 cph single-sided & 1500 cph dual-sided
- Programmable card cleaning to help maintain quality
- Can operate as a stand-alone unit with keyboard



NETWORK AND ENCODING

- Supports Ethernet and Serial connectivity
- Options for magnetic encoding & smart card personalization
- Contact, Contactless or both



EASY-TO-USE

- 500 card auto-feed input hopper & auto-unload stacker
- LCD screen displays printer status and diagnostics
- Easy to change ribbon and thermal print head
- Clear card support is standard

CONSULTING

SOFTWARE

HARDWARE


SMART CARD MANUFACTURING



| Single/Dual-sided | Fast, monochrome printing single-sided and double-sided printing |
|------------------------|---|
| Print method | Thermal transfer (mono) |
| Card encoding options | SmartSys [™] Tabletop batch Ussuance software designed especially for NBS desktop card printers, Magnetic encoding: 3 track, Dual Coercivity, ISO 7811, Bit to Bit (binary), Smart Card ISO 7816 personalization, Thin card kit for 0.015" (0.38mm) and 0.020" (0.51 mm) cards, Contactless (RF) Mifare card |
| Warranty | 12 month |
| Printer interfaces | Two-line, 40-character LCD |
| ••••• | Keyboard for manual data entry, RS-232C Serial 9 Pin; Ethernet 10/100bT, TCP/IP printing using LPR/LPD or Raw socket |
| Software drivers | Supports online printing from a variety of host computers including PC running Microsoft Windows 7, XP and AS-400 |
| | Supports both internally generated layouts using ASCII text fields from host computer, or full Microsoft Windows® compatibility with Windows 7, Windows XP and Windows 2000 drivers. |
| | Supported by NBS SmartSys™ Tabletop machine control software, a user-friendly, Windows card design and production application, ideal for batch issuance. |
| Fonts/Images | 300 dots per inch (11.8 dots per mm) resolution. Full range of monochrome color ribbons (full and half widths) available. |
| | Shipped with Swiss Regular: 6, 8, 10, 14, 18, 24 pt, Swiss Italics: 6, 8, 10, 14 pt, OCRA: 10, 12 pt, Dutch Bold: 6, 8, 10, 18, 24 pt, Any True-Type font can be downloaded from Microsoft Windows to support customized fonts |
| | PC Dash Board software for use in downloading additional fonts and images also used for flash loading of firmware for easy updates. It also can be used to back the machine settings. |
| Barcodes | EAN 13 & 8, UPC-A, Code 39, Codabar, Code 128, Code I 2 of 5 |
| Card capacity | 500 - auto-card feeder input hopper, 500 - auto-unload stacker, 25 - reject tray, Two production counters, one re-settable |
| Weight | 70 lbs (31.8kg) |
| Power source | 110-230 Volts, 50-60 Hz FCC Class B, CE and ETL approved |
| Dimensions | 16" (407mm) D x 24" (610mm) W x 23" (585mm) |
| Environment | Operating temperature: 15°C to 30°C, Relative humidity: 20% to 65% non-condensing, Storage temperature: -5°C to 70°C, Storage humidity: 20% to 70% non-condensing, Ventilation: Free air |
| Monochrome Print speed | Single-sided: Up to 4000 cards per hour, Dual-sided: Up to 1500 cards per hour |
| ••••• | Automatic card cleaning mechanism with user configurable cleaning |

Card Specifications

| Types | PVC & composite PVC - including breakaway and key cards |
|--------------------|---|
| Maximum print area | 0.100" +/- 0.010" from side edges of card01 |
| Card width/length | ISO CR-80-ISO 7810: 53.98mm (W) x 85.60mm (L) / 3.375" x 2.125" |
| Card thickness | 0.024" (0.61 mm) to 0.030" (0.76mm), (Optional)Thin card kit for 0.015" (0.38mm) and 0.020" (0.51 mm) cards |





The ImageMaster D-40 works in line with our NBS-1500 Mailing System to create a <u>low-cost</u> issuance & fulfilment system.





Corporate Headquarters Canada 703 Evans Avenue Toronto, Ontario M9C 5E9

Canada tel: +1 416.621.1911 fax: +1 416.621.8875 Contact our NBS card personalization experts for full details on this and other card personalization products at:



Europe, Middle East, Africa B1 Moorfield Point Slyfield Industrial Park Guildford, Surrey GU1 1RU United Kingdom

United Kingdom tel: +44 (0)1483 563200 fax: +44 (0)1483 511189 North / South America 10925 Bren Road E Minneapolis, MN 55343 USA

tel: +1 416.840.8620 fax: +1 952.912.9439 Asia Pacific PO Box 780 Hurstville BC NSW 1481 Australia tel: +61 (2) 9546

tel: +61 (2) 9546 6841 fax: +61 (2) 9546 6851