P120i™ Card Printers





single-sided printer pricing

Now you can affordably take advantage of the space on the back of your cards. The Zebra® P120i is the most affordable dual-sided, full color card printer in an industry-leading compact design. Ideal for space-constrained environments, Zebra's P120i brings you dual-sided printing at an unprecedented price.

Load-N-Go™ Ribbon Cartridge

Load-N-Go ribbon cartridge with integrated card cleaning roller for easy ribbon replacement

Ideal for • Employee ID cards

- Student and faculty ID cards
- · Access control cards
- Membership and loyalty cards
- · Personalized gift cards
- Visitor ID cards



Specifications at a Glance*

General Specifications

- Integrated feeder-and-flipper
- Load-N-Go[™] drop-in ribbon cartridge
- · 16-character LCD display
- Windows® drivers: 2000, XP, Server 2003; Vista compatible
- · 100-card covered holder
- · Two year printer warranty
- Two year (unlimited passes) original printhead warranty

Printing

- Color dye sublimation or monochrome thermal transfer printing
- 40 seconds per card full-color dual-sided (YMCKOK)*
- 30 seconds per card full-color single-sided (YMCKO)**
- 300 dpi (11.8 dots/mm) print resolution
- ** Based on average print coverage per card, under certain conditions.

Bar Codes

- Code 39, Code 128 B & C with & without check digit
- 2-of-5 & 2-of-5 Interleaved

Compact and Flexible

the counter

monochrome

Easy to Use

messaging

required!

reduces training costs

into a wide range of locations

• Weighs less than 10 pounds (4.3 kg)

· The smallest footprint in its class—easily fits

Conveniently fits on the desktop or under

· Print single-sided or dual-sided, color or

· Intuitive design simplifies set-up and

· LCD screen provides printer status and error

Translucent card cover allows you to see

Simple printhead replacement—no tools

when card supply is running low

- UPC-A, EAN 8 & EAN 13
- PDF417 2-D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- Types: PVC, PVC Composite
- Card width/length: ISO CR-80-ISO 7810, 2.12" /54 mm x 3.38"/86 mm
- Magnetic Stripe—ISO 7811
- Card thickness: 30 mil (.76 mm)
- Card feeder capacity: 100 cards (30 mil)
- Card output hopper capacity: 45 cards (30 mil)

Communications Interface

- USB 1.1 (USB 2.0 compatible) cable included
- Optional built-in 10/100 Ethernet

Ribbon Specifications



- Load-N-Go ribbon cartridge with integrated card-cleaning roller
- i Series™ intelligent ribbon technology
- YMCKOK: 165 cards/cartridge
- YMCKO: 200 cards/cartridge
- Monochrome: 1000 cards/cartridge black, blue, red, green, gold, silver, 850 cards/cartridge white
- For optimum printer performance use genuine Zebra supplies

Mechanical

Width: 7.9"/201 mm
Depth: 12.9"/328 mm
Height: 9.25"/235 mm
Weight: 9.5 lbs/4.3 kg

Reliable Performance

- Made with high-strength plastics for reliability and lower maintenance costs
- Integrated card feeder/flipper minimizes printer size while maximizing performance
- Optional magnetic stripe encoding (HiCo/LoCo)

i Series™ Functionality

- Automatic color optimization and driver configuration
- Enhanced ribbon formulation for optimal color output
- Ribbon image counter and ribbon-low notification

Electrical

- + 100 \sim 240 Volts AC, 50 \sim 60 Hz (auto switching)
- 8MB image memory standard
- FCC Class A, CE, UL, CUL, and CCC approved

Environmental



- Operating Temperature: 60° F/15° C to 86°F/30° C
- Operating Humidity: 20% to 65% non-condensing
- Storage Temperature: 23° F/-5° C to 158° F/ 70° C
- Storage Relative Humidity: 20% to 70% non-condensing
- · Ventilation: Free air

Options

- Built-in 10/100 Ethernet
- Magnetic encoder (30 mil cards only), 3 track HiCo/LoCo
- CardSense[™] single-feed kit
- Starter Kit (200 30 mil PVC cards and 1 YMCKO ribbon)
- Cleaning Kit (4 print engine and 4 feeder cleaning cards)

Genuine Zebra™ Supplies

Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.



For more information, visit www.zebracard.com

*Specifications subject to change without notice

©2008 ZIH Corp. CardSense, Load-N-Go, i Series and all product names and numbers are Zebra trademarks, and Zebra and the Zebra head graphic are registered trademarks of ZIH Corp. All right reserved. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.





photo identification for less
www.IDWholesaler.com
(800) 321-4405
SHOP NOW

IDWholesaler.