

FlexSmart® 13.56 MHz Contactless – Credentials



Base Part Number	MIFARE® Card	MIFARE® / HID Prox Combo Card	MIFARE® / Indala® Prox Combo Card	DESFire® Card	DESFire® / HID Prox Combo Card	DESFire® / Indala® Prox Combo Card	MIFARE® Keyfob	DESFire® Keyfob	MIFARE® Adhesive Tag	DESFire® Adhesive Tag
	I430 ; PVC 1k Card	I431 ; PVC 1k Card	FPMXI ; PVC 1k Card	I450 ; PVC Card	I451 ; PVC Card	FPDXI ; PVC Card	I434 ; 1k Keyfob	I454	I435 ; 1k Tag	I455
	I440 ; PVC 4k Card	I441 ; PVC 4k Card	FPMXX ; Composite PET/PVC 1k Card	I456 ; Composite PET/PVC Card	I457 ; Composite PET/PVC Card	FPDXX ; Composite PET/PVC Card	I444 ; 4k Keyfob		I445 ; 4k Tag	
	I436 ; Composite PET/PVC 1k Card	I437 ; Composite PET/PVC 1k Card								
	I446 ; Composite PET/PVC 4k Card	I447 ; Composite PET/PVC 4k Card								
Read Range: *										
MIFARE	Up to 4"				N/A		Up to 2"	N/A	Up to 2"	N/A
DESFIRE	N/A				Up to 4"		N/A	Up to 2"	N/A	Up to 2"
HID Prox	N/A	Up to 4.5"	N/A		Up to 4.5"		N/A			
Indala Prox	N/A		Up to 4.5"		N/A		Up to 4.5"		N/A	
Memory Size/ Application Areas	1k Byte (8,192 bits) or 4k Bytes (32,768 bits)				4k Bytes (32,768 bits)		1k Byte (8,192 bits) or 4k Bytes (32,768 bits)	4k Bytes (32,768 bits)	1k Byte (8,192 bits) or 4k Bytes (32,768 bits)	4k Bytes (32,768 bits)
HID Proximity 125 kHz	No	Yes	No		Yes	No				
Contact Smart Chip Module Embeddable			Yes				No		Yes	
Wiegand Strip	No									
Magnetic Stripe			Optional						No	
Printable **			Yes						No	
Slot Punch			Vertical optional				Key Ring Hole		No	
Visual Security Options			Yes						No	
Warranty	Lifetime									

* Dependent upon installation conditions.

** Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.

FlexSmart

IDWholesaler
We know ID. It's what we do.



www.IDWholesaler.com
(800) 321-4405 x2

Shop Now