





# Introduction

The Tactile Impression Feature is an advanced security feature available exclusively on the Datacard<sup>®</sup> SD460<sup>TM</sup> card printer and CD800<sup>TM</sup> card printer with inline lamination module. This unique feature can be combined with laminates and overlays to provide

the right level of security for your card program.

There are several options for you to consider when purchasing the tactile impression feature. Generic designs, representing multiple market segments, have been created and are currently available for ordering. Additionally, you have an option to create a unique, custom design specific for your ID card program. The



tactile impressions can contain text, logos, and outlines of images that may vary in design and complexity.



This guide will outline the requirements for creating a custom design and help you determine how the tactile impression feature can enhance the security of your card program and promote your brand.


Review this guide completely as all of the design elements impact your card design in different ways.






#### **Card Layout Recommendations**

There are several things to consider when determining where to place the tactile impression on your card. Ideally, you want to have the impression cover part of a variable photo or text to maximize the tamper evidence of personalized data on the card.





#### Track 1, 2 and 3

- There are 3 tracks defined in the design of the card: Track 1, 2 and 3
- Think of the tracks as guidelines for the center of the design.
- The tactile impression can be moved along any of those three tracks
- The design can be impressed numerous times along the tracks


#### Sections of the Cards

- There are three sections noted on the card image: Section A, B and C.
- The center of any impression made on the card has to be in Section B, to the right of yellow line noted in the card image.
- The image may overlap into Section A or C, as noted in the image above.





- The impression may move slightly on each card as it passes through. The variability differs by section
  - Section A: +/- 0.010in (.25mm)
  - Section B: +/- 0.040in (1mm)
  - Section C: +/- 0.080in (2mm)
- This may become important if the card being impressed has an antenna. Account for this potential variance when determining the location of the impression and the location of the antenna.



**IMPORTANT NOTE**: There is variability in the location of the antenna or smart chips in every card. We recommend you check with the manufacturer of the card for exact location and variance.


In addition, we also recommend you do not impress over OCR text or bar codes.





#### **Card Layout Examples**


Below are X-ray image examples of commonly used smart cards. These are for reference only and should not be used to decide placement of the tactile impression for your card program. We recommend you check with the manufacturer of the card for exact location and variance.




Oberthur card for 14443 Type B




GemPlus (Gemalto) card for ISO14443 Type B



G & D card for ISO14443 Type A



CPI card for ISO14443 Type B





### **Recommended Card Types**

The tactile impression feature was designed exclusively for the SD460 printer and CD800 printer with lamination and it is recommended that the tactile impression feature is used with card technology compatible with the SD and CD series of card printers. The depth of the impression can be adjusted on both to impress on different types of cards. Refer to the installation manual for directions on setting or changing the dwell depth for your card.


### **Recommended Durability and Security Solutions**

There are a wide variety of laminates and overlays that can be used with the tactile impression feature. Clear overlays and laminates provide the durability required to protect and extend card life for a range of card use applications. To enhance security, the tactile impression feature can be paired with any of our Datacard<sup>®</sup> DuraShield<sup>TM</sup> Overlays or DuraGard<sup>®</sup> Laminates featuring Datacard<sup>®</sup> Opti Series Security Features. From basic offerings that provide lower minimum order requirements, to complex designs for programs requiring the utmost security, we can deliver solutions you need to help ensure a successful ID card program. Note: The depth may need to be adjusted based on the type of material used. Refer to the installation manual for directions on setting or changing the dwell depth for your card.

# **Design Orientation**

When designing a custom tactile impression, consider the orientation of the design, and whether or not you will be printing multiple card types with both portrait and landscape orientations. Once the die is inserted in the tactile impresser module, it can't be rotated based on card orientation.

If you select a die that has to be oriented one way or the other, and you use both portrait and landscape orientations, the design may not be desirable.





In the following cards, the tactile impression design is designed for a card with a landscape design, and when printed on a vertically oriented card, the impression does not rotate.





With a more symmetrical design, the tactile impression can fit both landscape and portrait orientations.



# Tactile Impression Diameter

There are two options to choose from when selecting the size of your tactile impression. The size you select will determine the amount of detail you will be able to design into the impression.



#### Actual Size



.85 inch (2.159 cm)

#### Enlarged








The diameter of the impression should also be considered when designing your card. A smaller impression may work better if you want to repeat the design multiple times, or if there are areas of the card that need to be avoided.

#### **Tactile Impression Shape**

The design of the impression can be any size or orientation, as long as it fits in the diameter of the impression size selected.

#### Examples of potential designs.



#### **Tactile Impression Design**

The tactile impression feature can be a design, text or a combination of both. This gives you an opportunity to use the impression to highlight and promote your brand, or make the card more easily identifiable and unique to your program.

#### **Image Requirements**

The following guidelines provide more detail on the design of a custom tactile impression feature. These guidelines and recommendations will ensure you get the best impression for your card program.

- 60 dpi
  - Line Thickness .005-.010 inch (0.127-0.254 mm)
  - Space between features .020-.025 inch (0.508-0.635mm)

 60 DPI grid overlaid on Punch Design




There is limited ability to reproduce fine lines, so that should be considered in your design.



Sharp inside corners should be avoided, as they won't translate well onto the die. All corners should have a .005 inch (.127 mm) radius.

Example:



Solid areas may need to be reduced to an outline only (as shown in the elements below) in order to achieve crispness in the tactile impression. The maximum amount of protruding surface area is 0.12in (3.048mm) for a 0.85in (21.59mm) die.



To help ensure tamper evidence and tear resistance, we strongly recommend adding a broken circular feature around the outside of the impression as noted below.








#### **Text Requirements**

The spaces between characters should be 120%-200% larger than default (depending on font). This is to accommodate for .020in-.025in (0.508-0.635mm) of space required between all features




All capital letters are required, as most lower-case letters are not possible.

The minimum text size is 0.60in (1.52mm) Minimum height requirement:

- Approximately 35-40 characters will fit in the 0.85in (21.59mm) die, depending on font

- Approximately 15 characters will fit on a straight line on a 0.85in (21.59mm) die, depending on font



**IMPORTANT NOTE:** The above text requirements are based on Romanized characters. Non-Romanized characters will need to be tested on a case-by-case basis. These still require the .020in-.025in (0.508-0.635mm) of space between all features. For example, the spaces circled in red below need to maintain this .020in (0.508mm) minimum spacing.







### **Design Conversion**

The tactile impression feature is intended for relatively simple designs. Shading on the tactile impression is not possible, and complex designs will be simplified when developed. Consider this when choosing an image to submit for your custom die program.

Below are design examples with varying levels of complexity, to show how artwork is simplified in the resulting die design, based on our image and text requirements.

| Artwork    | Die Card View                            | Requirements                        | How design was simplified   |
|------------|--|-------------------------------------|---|
| UNIVERSITY | UNIVERSITY<br>DUCO<br>000<br>1833<br>000 | .020" (0.508mm)<br>Spacing          | <ul> <li>"University" and "1833"<br/>spaced</li> <li>Leaves spaced</li> </ul> |
|            |  | 0.12" (3.048mm)<br>Max Surface Area | • "U" and ribbons reduced to outline  |
|            |  | Font Specification                  | • Changed to Calibri, as no font specified on order form                      |

*Example 1:* This level of complexity is acceptable, with minimum changes needed.

Example 2: This level of complexity can work, but many elements need to be reduced.

| Artwork | Die Card View                         | Requirements                                | How design was simplified   |
|---------|---------------------------------------|---|---|
|         | A A A A A A A A A A A A A A A A A A A | .060" (1.52mm)<br>Minimum Text Size         | • Text in ribbon removed  |
|         |                                       | .020" (0.508mm)<br>Spacing                  | <ul> <li>Outer circle reduced</li> <li>Several design elements removed</li> </ul> |
|         |                                       | .005010"<br>(0.127-0.254)<br>Line Thickness | • Dots enlarged and reduced   |
|         |                                       | 35 characters around<br>.85" (21.59) die    | • Outer ring of text reduced  |

Example 3: This level of complexity is not recommended, as significant elements must be removed.

| Artwork  | Die Card View  | Requirements                             | How design was simplified  |
|--|--|--|--|
| A LOS THEST THE STATE OF THE ST | TATE OA<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL<br>STONAL STONAL STONAL<br>STONAL STONAL STONAL STONAL<br>STONAL STONAL S | .060" (1.52mm)<br>Minimum Text Size      | • Text in ribbon removed   |
|  |  | .020" (0.508mm)<br>Spacing               | <ul> <li>Dots enlarged and reduced</li> <li>Landscape reduced</li> <li>Several elements removed</li> </ul> |
|  |  | 35 characters around<br>.85" (21.59) die | • Outer ring of text reduced   |






## **Ordering Your Custom Tactile Impression**

The process for ordering a custom tactile impression is very similar to ordering a custom holographic overlay. We have developed an order form that will allow you to provide the information we need to design the tactile impression feature. All artwork should be submitted as a vector file: .DXF (Drawing Exchange File) or Adobe Illustrator file.

The development of the artwork for approval will take approximately 5-10 business days from receipt of artwork files, depending on the complexity or the number of revisions.

Once the design is approved, delivery of the tactile impression die will take approximately 20 business days.



#### **Generic Tactile Impression Feature**

We have several generic designs to choose from. All of the items are stocked in our warehouse, ready for installation and shipment when you order your new SD460 card printer or CD800 printer with lamination. Please refer to the Generic Tactile Impression Design Overview for details on our generic die offerings.

### Installation of Your Tactile Impression Die

All tactile impressor modules are shipped from the factory with a default "D" impression die installed, unless a generic or custom die are ordered with the tactile impressor module.

There are two options for receiving and installing the generic or custom tactile impression die.

Option 1: Installation at the factory. If this option is selected, the printer will ship with the tactile impressor module and the die already installed. Since generic dies are available from stock, there will be no delay to your order for selecting this service. If a custom tactile impression die is ordered, your orders will be held at the factory until the custom die is available. Additionally, at this time, factory installation is only available from the hub in Minneapolis, Minnesota, U.S.A. There is a fee for this installation. Please refer to Price Pages for current pricing.





Option 2: Installation via a Datacard Channel Partner. If installation by a Datacard Channel Partner is selected, the printer will ship separately from the generic or custom die. Since generic dies are available in stock, the printer and generic die should be shipped at approximately the same time.

Custom dies have a longer lead time as noted, so there will be a lag between printer and die shipment.

#### Summary

The tactile impression feature is a great addition to the suite of security options available from Datacard.

To order your custom tactile impression die, refer to the Tactile Impression Order Form.



Datacard, SD460, CD800, DuraGard, and DuraShield are trademarks, registered trademarks and/or service marks of DataCard Corporation in the United States and/ or other countries.

© 2015 Entrust Datacard Corporation. All rights reserved. Specifications subject to change without notice.

